Offers protection from falling impact hazards such as bricks, tools and materials. It is recommended that helmets are replaced at a maximum interval of five years. This interval should be greatly reduced for helmets that have been exposed to extensive wear and tear, left in the sun, written on or have had any labels stuck on that do not have the correct adhesive. Helmets that have been damaged i.e. cut or scratched should be replaced immediately. Helmets should be regularly inspected for damage.



Standard Harness:

A resilient plastic cradle which is adjustable to fit a range of head sizes from 50 to 66cm.



Colour	each	SSF-957
Green		-1000K
Grey		-1010K
Orange		-1020K
Red		-1030K
Royal Blue		-1040K
White		-1050K
Yellow		-1060K

Comfort Harness:

A comfortable six-point terylene head harness and sweatband which is adjustable to fit a range of head sizes from 50 to 66cm.



	Colour	Weight each	Order Code SSF-957
	Green		-1100K
	Grey		-1110K
	Orange		-1120K
	Red		-1130K
F	Royal Blue		-1140K
	White		-1150K
	Yellow		-1160K

RUTLAND Professional Safety Helmets

Lightweight, stable and comfortable fit with less leverage on the head and a lower centre of gravity, making it feel even lighter than it is. Short peak for enhanced visibility. The new DeFormaTecTM system reacts ultra quickly to absorb impact energy before it reaches the wearer. The helmet shell is a result of analysis of thousands of helmet crash tests. It is based on the same principle as a rigid yet flexible Formula 1 chassis, reacting on impact by partial deformation to absorb the shock. Conform to **EN 397: 1996.**

Fitted with a four point adjustable comfort webbing harness and absorbent soft leather sweatband.



Colour	Weight each	Order Code RTL-957	
White Yellow	325g 325g	-0400K -0420K	

European Directive 2003/10/EC 15th February 2006

The above regulations require employers to provide suitable ear protection to employees that are working in noise levels between 80dB and 85dB on request. If noise levels rise above this then ear protection must be worn. Regulation 8 states that when not in use items should be stored in proper accommodation i.e. lockers etc. Regulation 9 states that employees must be fully trained in the use of any PPE equipment supplied. Noise can be unpleasant, sometimes dangerous and can cause permanent damage over a period of time so correct hearing protection is imperative.

SNR = 31dB

H = 34dB

M = 29dB

L = 20dB

Choosing the Right Hearing Protection

All products throughout this section have a Standard Noise Reduction (SNR) rating to help you choose the right hearing protection. First of all the working environment noise level must be established for you to then calculate which SNR rating you require.

Example:

Working in an environment with a 100dB noise level requires hearing protection of 20dB - 25dB to bring the noise level in to the safe zone of below 80dB.

Care must be taken not to over protect as this can also be hazardous in the work place i.e. not being able to hear forklifts and verbal instructions/warnings.

Protection Markings Chart Harmful Range Jet Engine 130 **Riveting Hammer** 120 **Propeller Aircraft** 110 **Rock Drill** 100 **Plate Fabrication Shop** 90 **Heavy Vehicle Upper Action Level Busy Traffic Lower Action Level** 80 70 **Private Car**

Conversation

PROTECTION AT WORK Defenders

Hearing

With Flexible reinforced plastic headbands ABS cups and PVC cushions. Conform with EN 352-1: 1993.





Duty Type	Order Code KEN-958	
General	-1000K	

Folding Hearing Defenders

Hazardous Duty Type

Fold-away design with telescopic arms. Conform with EN3521: 1993.



Disposable **TUFFSAFE** Ear Plugs

Hexagonal foam plugs. Conform with EN 352-2:1993. Supplied as pairs, individually packed in polythene pouches. Tested and approved by **INSPEC**.

Box = 200 pairs.

29dB H = 32dBM = 25dBL = 20dB



Model	Weight	Order Code	
Number	per pk	TFF-958	
HEP029	380g	-0010K	

Banded Ear Plugs

Durable plastic headband equipped with soft, flexing pads adjusting to jaw and head movements. It can be worn under the chin or behind the head. Arms pivot for maximum comfort. Suitable for intermittent wear as the ear plugs do not need to be rolled to be fitted allowing easy insertion.



21dB

Туре	Order Code TFF-958	
Banded	-0200K	

Ear Plugs & Dispenser

The dispenser is supplied with 1,000 TuffSafe® cordless earplugs (Refill order code: TFF-958-9020K). The dispenser is designed for durability and ease of use in the workplace; earplugs are dispensed singly simply by twisting the nozzle, the clear container allows the contents to be seen at all times helping to ensure, you do not unexpectedly run out of earplugs. The dispensers can either be fixed to a wall or stood on a workbench; anywhere you require them to be close at hand.

TuffSafe® Ear plug specification:

Cordless type, disposable for comfortable hearing protection without impairing normal communication.

SNR: 37Db.

SNR =

Product conforms to EN352-2: G2002. Nominal size: smallest: 6, largest: 12.

Description	Order Code TFF-958
Dispenser + 1000 Plugs Refill (1000 Plugs)	-9010K -9020K

Disposable Ear Plugs

Premium

High protecting shaped foam ear plugs which provide maximum comfort with excellent attenuation, the smooth tapered finish makes fitting easier and helps form a comfortable fit. These ear plugs give evenly distributed pressure, flexibility and a good seal with optimum comfort. Conform to CE0194EN352-1:1993.



Corded Ear Plugs

Shaped foam corded ear plugs with red cord for maximum visibility, comfort and protection, the smooth tapered finish makes fitting easier and helps form a comfortable fit. These ear plugs give evenly distributed pressure, flexibility and a good seal with optimum comfort. Conform to









Selection of Respiratory Disposable Products

There are three types of protection standards -

P1: Lower or basic level - choice

with/without valve.

P2: Intermediate - choice with/without valve.

P3: Highest level of protection available only with valve. The valve reduces heat and moisture build-up which improves comfort

for the wearer.

Common Respiratory Hazards

Dusts: Created when solid materials are totally or partially reduced to smaller particles, they are more easily inhaled the longer they stay in the atmosphere.

Fumes: These will generally be created when materials/metals vaporise in high temperature conditions which then cool rapidly thus condensing into

very fine particles.

Gases: Which are airborne at room temperature and are able to move about rapidly into any space within a short period of time.

Vapour: Are given off by materials that are generally liquids or solids at normal room temperature.

Terminology used in **Respiratory Protection**

W.E.L.: Workplace Exposure Limits These are two types occupational exposure standards or maximum exposure limits.

O.E.S.: Occupational Exposure Standards

These are levels for a substance for which the majority of employees may be exposed to for an eight hour day, five days a week. Exposure to a substance assigned as O.E.S. can be exceeded, however steps need to have been identified to show exposure will be reduced.

M.E.L.: Maximum Exposure Limits

These limits are generally accepted as the maximum exposure periods that people should be exposed to substances which can result in very serious types of cancer, occupational asthma etc. Exact safe levels of exposure cannot be identified, and caution should be used when exposed to these substances.

The M.E.L. should never be exceeded and exposure reduced to as low as is reasonably practicable whenever possible

Protection Factors for Respiratory Protection

N.P.F.: Nominal Protection Factor

These protection factors are extracted from the performance data categories of the European Standards to which all respirators are tested. These should not be used to select R.P.E.

A.P.F.: Assigned Protection **Factor**

These are deduced from many workplace protection factor studies as laid out in the British Standard BS 4275.

These should be used in product selection decisions.

R.P.E.: Respiratory Protective **Equipment**

Each type of respiratory protective equipment has specific limitations relevant to its use and these dictate, along with the design, what type of application and conditions are best suited to each specific product.

Your Tuffsafe distributor is able to supply and give advice on all respiratory protection issues

Particulate TUFFSAFE® **Respirator Mask**

DRV 350

With unique design provides very low breathing resistance, polypropylene (PP) outer layers provides smooth lining and avoids loose fibres, fringe seal avoids open layer around the edges, adjustable headstrap ensure the best seal with minimum leakage, contour design ensures the compatibility of glasses/goggles and reduces fogging, full facial close-cell nose foam and adjustable nosepiece ensures custom shape and increase the worker comfort and acceptance. With exhalation valve for breathing easier and reduce hot air build-up. For protection from high toxicity harmful solid and liquid aerosols containing the following materials in concentrations up to 50 x NPF or 20 x APF, such as calcium carbonate, china clay, cement, cellulose, sulphur, cotton, flour, carbon, ferrous metals, vegetable oils, hardwood, glass fibres, plastic, carbon, mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB), chromium, manganese, nickel platinum, strychnine, metal dust and smoke, viruses and enzymes. Recommended applications: textile industry, craft work, iron and steel industry, mining, underground civil engineering, woodworking, welding work, cutting and casing of metals, hospital, laboratory and

disease control, pharmaceutical industry. Disposal of toxic waste, manufactured of batteries (Ni-Cad) etc. Conforms to EN149 2001 standards.

NPF = Nominal Protection Factor. APF = Assigned Protection Factor.

Product Order Code Pack Quantity TFF-959 DRV350 5 -2350K

Particle Respirator Mask

Conforms to EN149 2001 FFP2 standards.

With polypropylene (PP) outer layers provides smooth lining and avoids loose fibres, fringe seal avoids open layer around the edges, latex-free synthetic rubber head strap, contour design ensures the compatibility of glasses/goggles and reduces fogging, soft close-cell nose foam and adjustable nosepiece ensures custom shape and increase the worker comfort and acceptance. With exhalation valve for breathing easier and reduce hot air build-up. For protection against low-to-average toxicity harmful solid, liquid and smoke containing the following materials in concentrations up to 12 x NPF or 10 x APF, such as calcium carbonate, china clay, cement, cellulose, sulphur, cotton, flour, ferrous metals, vegetable oils, hardwood, glass fibres, plastic, carbon, mineral oils, quartz, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB). Recommended applications: textile

industry, craft work, iron and steel industry, mining, underground civil engineering woodworking, welding work, cutting and casing of metals, hospital, laboratory and disease control etc.



APF = Assigned Protection Factor.

Product Protection Pack Weight Order Code NPF Number Quantity each **DRV212** -2310K

TUFFSAFE®

Particulate Respirator Mask

DRM212

With polypropylene (PP) outer layers provides smooth lining and avoids loose fibres, fringe seal avoids open layer around the edges. Latex-free synthetic rubber head strap, contour design ensures the compatibility of glasses/goggles and reduces fogging, soft close-cell nose foam and adjustable nose-piece ensures custom shape and increase the worker comfort and acceptance. For protection against low-to-average toxicity. harmful solid, liquid and smoke containing the following materials in concentrations up to 12 x OEL or 10 x APF, such as calcium carbonate, china clay, cement, cellulose, sulphur, cotton, flour. ferrous metals, vegetable oils, hardwood, glass fibres, plastic, carbon, mineral oils, quartz, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB). Recommended applications: textile industry, craft work, iron and steel industry, mining, underground civil engineering, woodworking, welding work, cutting and casing of metals, hospital, laboratory and disease control etc. Supplied in packs of 20.



NPF = Nominal Protection Factor. APF = Assigned Protection Factor.

Product Number	Protection Level	OEL	Pack Quantity	Weight each	Order Code TFF-959
DRM212	FFP2	12	20	10g	-2110K

Particulate Respirator Mask

DRV104

Exhalation valve for extra comfort in hot and demanding conditions. Adjustable nose piece. Maintenance-free (disposable). Easy breathing/speaking.



NPF = Nominal Protection Factor. APF = Assigned Protection Factor.

Product Number	Pack Quantity	Weight each	Order Code TFF-959	
DRV104	10	14g	-2210K	

RESPIRATORY PROTECTION

Particulate Respirator Mask

DRM104

Adjustable nose piece, Soft nose foam. Maintenance-free (disposable). Easy breathing/speaking.





NPF = Nominal Protection Factor. APF = Assigned Protection Factor.

Product	Pack	Weight	Order Code	
Number	Quantity	each	TFF-959	
DRM104	20	8g	-2010K	

Nuisance Dust Mask

TCM50

Reduces discomfort caused by non-toxic nuisance dust. Lightweight and comfortable to wear, adjustable nose piece. Maintenance-free (disposable). Easy breathing/speaking.



Application Information

Nuisance dust masks should not be used to protect your lungs, or used where a device complying with the European Directive 89/686 or 89/656 is required.

It is not classified as a respiratory protective device and falls outside the PPE (EC Directive) Regulations. These products should not be used to protect against fine dust particles, toxic gases and vapours.

Product Number	Pack Quantity	Order Code TFF-959
TCM50	50	-8050K

960 EYE & FACE PROTECTION

Quick Reference

Through the eye and face protection range, there are a number of quick reference logos to help you choose which level of safety is right for you. Below are the logos and their meanings.



Adjustable frames for a superior fit.



Wrap around single lens provides unobstructed field of vision.



Resistant to flames and heat not flame-proof.



Designed to minimise dust contamination.



Polycarbonate lenses are more impact-resistant and lighter than most types of lens.



Has a lower impact energy rating and is more flexible compared to polycarbonate.



This provides increased safety, while retaining excellent visibility.



Gives a level of protection against harmful UV rays.

Protection Markings Chart



Extended brow guard moulded into the top of the lens gives a near perfect orbital seal against debris.



For greater protection from debris towards the side of the eyes.



Glasses which have a larger lens to cover the cheek bone.



Resistant to chemical splashes not chemical proof.



Hard coated for excellent durability and scratch resistance resulting in unobstructed viewing.

BS EN166

Lens

Lens

THE PARTY

Donate attended and the second	BS EI	N166
Protection Markings Chart	Frame	Lens
Optical Class:		
Refractive tolerance +0.06 dio		1
Refractive tolerance +0.12 dio		2
Refractive tolerance +0.12/-0.25 dio		3
Mechanical Strength: Minimum Robustness		
Increased robustness (velocity <12 m/s)		S
Low-energy impact (velocity <45m/sec)	F	F
Medium-energy impact (velocity <120m/sec)	B	В
High-energy impact (velocity <190m/sec)		
Field of use: Basic		
Droplets and Splash of Liquids (chemical)		3
Large dust particles (dust)	4	

Gas and fine dust particles (gas)5 Short circuit electric arc Molten metals and hot solids9 Optional extras Resistance to misting.....N Resistance to surface damage (anti-scratch)K Lens Marking: **Code Number:** Indicates the type of filter 2 and 3 = UV 4 = IR 5 and 6 = solar). Shade number: Indicates the shade of the lens (between 1.2 and 7 for spectacles and goggles). Identification of the manufacture: (D = Pulsafe).

Scratch

KENNEDY Scratch Resistant Personal Protection Safety Spectacles

Low energy impact protection at extreme environmental temperatures. Scratch resistant coating for a longer Side lens life. UV protection. Clear polycarbonate lenses. Class 1 optical quality for distortion-free continuous

use. Integral twin nose bridge styling for user comfort. Raised nose bridge for extra lens protection when placed face down. Hang cord



-8000K

-8010K

Scratch Resistant Safety Spectacles

Ultra light nylon frame with added elasticity and sturdiness. Built in side shields for increased lateral protection. Scratch resistant clear polycarbonate lenses.



Anti-Scratch/Anti-Mist Safety Spectacles

Amber

Panther

Anti-Scratch

Low energy impact protection. Ultra light anallergenic frame with low friction length adjustment at the temples and front angle adjustment. One piece, anti-scratch, clear polycarbonate lens with built in side shields for increased lateral protection. Class 1 optical quality. Arms have hang cord attachment



Black


Anti-Scratch/Anti-Mist Safety Spectacles

Lens

Side

Scratch

Low energy impact protection. Ultra light anallergenic frame with low friction length adjustment at the temples and front angle adjustment. One piece, anti-scratch clear polycarbonate lens with built in side shields for increased lateral protection. Class 1 optical quality. Soft silicone nose bridge. Arms have hang cord attachment points.



Anti-Scratch/Fog

Wrop

Around



Anti-Mist Safety Spectacles

Azure

Moulded one piece wrap around anti-mist polycarbonate lens with multi-adjust, soft, non-allergenic nose bridge. Unobstructed peripheral vision.

Wire cored side arms for lateral adjustment.





Weight each Order Code TFF-960 Lens Frame Type Colour Blue -3500K Clear 30g

Anti-Mist Safety Spectacles

Azure E-M

Moulded one piece wrap around anti-mist polycarbonate lens with multi-adjust, soft, non-allergenic nose bridge. Wire cored side arms also feature lateral adjustment for maximum versatility and comfort.








Lens	Frame	Weight	Order Code	
Type	Colour	each	TFF-960	
Blue	Blue	35g	-3520K	

Spectacles





Frame Colour	Weight each	Order Code TFF-960	
Blue	35g	-4040K	

Wrap

Around

Brow

Wrop

Around

Lens

Brow

Wrap Around


Lens

Brow

Anti-Mist Safety Spectacles

Ice-G

Grey anti-mist wrap around polycarbonate lenses. One piece brow bar with soft comfort fit insert. Side arm comfort fit insert pads.






Frame	Weight	Order Code	
Colour	each	TFF-960	
Dluo	254	4020K	

Safety Spectacles

lce

Maintenance & Personal Protectio

Wrap round clear polycarbonate lenses. One piece brow bar with soft comfort fit insert. Side arm comfort fit insert pads.





Frame	Weight	Order Code	
Colour	each	TFF-960	
Blue	35g	-4000K	

THE REAL PROPERTY. Frame

Wrap

Around

Lens


Anti-Mist Safety Spectacles

Retro-R

Moulded one-piece wrap around anti-mist polycarbonate lens with multi-adjust, soft, non-allergenic nose bridge. No frame means maximum unobstructed peripheral vision. Side arms also feature lateral adjustment for maximum versatility and comfort.

CE approved to EN166F.

Supplied with neck cord.







Lens	Frame	Order Code
Type	Colour	SSF-960
Polycarbonate	Blue	-7400K

Anti-Mist Safety Spectacles

Luna

One piece clear polycarbonate lens with anti-mist treatment and ultra lightweight design (26g).

Built-in side protection with integral nose bridge adjustable temple length and lens inclination. Low energy impact protection with total UV protection.

Hang cord attachment points. Class 1.





Lens	Frame	Order Code	
Type	Colour	SSF-960	
Clear	Black	-6600K	

Anti-Mist Safety Spectacles

One piece amber tinted polycarbonate lens with antimist treatment and ultra lightweight design (26g). Built-in side protection with soft silicone nose bridge and adjustable temple length. Low energy impact protection with total UV protection. Hang cord attachment points. Class 1.











Lens
Туре
Amber tint

Frame Black

SSF-960 -5200K



Anti-Mist Safety Spectacles

Saturn

One piece clear polycarbonate lens with anti-mist treatment. Lightweight black nylon frame with built-in brow guard. Built-in side protection with integral nose bridge and adjustable temple length. Low energy impact protection with 400nm UV protection. Hang cord attachment points. Class 1.





Adjustable Frame



-7600K

Frame

ens

Side Shields

Brow Guard

Anti-Mist Safety Spectacles

Mercury

One piece clear polycarbonate lens with anti-mist treatment. Lightweight black nylon frame with built-in brow guard. Built-in side shields with integral nose bridge and adjustable temple length. Low energy impact protection with UV protection.



CE SP

Lens Туре Clear Frame Colour Black

SSF-960 -7000K

Wrap

Around

Lens

Scratch

Wrap

ens

cratch

KENNEDY Safety Specs PERSONAL PROTECTION Scratch Resistant

Low energy impact protection. Polycarbonate wrap-around frame with low friction length adjustment at the temples and front angle adjustment. One piece, scratch resistant, polycarbonate lens. Class 1 optical quality. Arms have hang cord attachment points.

Cheetah Green Shade 5 Lens Tint

For use by welding helpers and for brazing only. Not for use with other welding techniques.




(€ & EN166 F

Lens	Frame	Order Code	
Type	Colour	KEN-960	
Green Shade 5	Black	-8020K	

Scratch Resistant Safety Spectacles

Viper UV protection against electrical arc discharges caused by a short circuit.





Lens Type	Frame Colour	Order Code KEN-960	
Clear	Blue	-8050K	

Scratch Resistant Safety Spectacles

Zenith

One piece wrap round polycarbonate spectacle which is light in weight and features hard coated clear anti-scratch resistant lenses.



Anti-Mist Safety Spectacles Voyager

Two piece clear polycarbonate lenses with anti-mist treatment. Built-in brow guard and side shields with integral nose bridge. Low energy impact protection with total UV protection. Class 1.





Frame Order Code SSF-960 Lens Type Colour Clear Black -8200K

960 EYE & FACE PROTECTION

TUFFSAFE Scratch Resistant Safety Spectacles

Mirage

Highly versatile and popular design featuring the unique sidearm adjustment ratchet which enables the wide vision one piece lens to be adjusted to meet the exact requirements of the wearer. Coated scratch resistant polycarbonate lens and side shields.





Lens

Side

Shields

Scratch

ram

Lens

Side

Shields

Scratch Resistant Safety Spectacles Selica

Attractive modern design consisting of a one piece nylon browbar fitted with a coated scratch-resistant polycarbonate lens. Lightweight nylon frame for extended use, comfort and strength. Easily replaceable, lens for safety, comfort and a wide field of vision. Unique light deflection bars on sideshields for additional wearer comfort.



		1	
8	Lens	Frame	Order Code
	Type	Colour	TFF-960

-1000K

Navv

Scratch Resistant Safety Spectacles

Vision

Lightweight modern safety spectacles with a one piece scratch resistant polycarbonate lens with integral sideshields. Two tone side arms feature a unique 'Vision' ratchet mechanism for angle adjustment (12 positions), closing off gaps for optimum protection.

EN166 F

Clear

Five position temple arm length adjustment with fixed end stop position. Brow and cheek guard protection.





KENNEDY Scratch Resistant/Anti-Mist Personal Protection Safety Spectacles

Leopard

Low energy impact protection. No metallic parts. Polycarbonate frame with adjustable temple length and built-in brow guard. One piece, anti-scratch, anti-fog clear polycarbonate lens with built in side shields for increased lateral protection. Class 1 optical quality. Ultra lightweight design.





iintenance & Personal Protectio

Wrop


Acound

Lens

RUTLAND Scratch Resistant Safety Spectacles

Rebel

A unique and stylish safety spectacle combining all the benefits of a wrap round design and a hard coated clear anti-scratch one piece lens. The Rebel offers the discerning wearer total eye protection which is light in weight with excellent facial fit.





Safety Spectacles

Ultimo

A radical approach to safety spectacle design. Featuring 10 base curve lens, stylish metal frame and designer style sprung side arms. Excellent design and fashionable styling.

Available with clear polycarbonate lenses.



Lens	Frame	Weight	Order Code
Type	Colour	each	RTL-960
Clear	Metallic	40g	-7740K

Safety Spectacles

A twin lens wrap round safety spectacle with hard coated lenses and burgundy soft frame coating for comfort and fit. Available with clear polycarbonate lenses.





C € 🕸	
EN166 F	
IS1706	

Туре	Colour	each	RTL-960	
Clear	Black		-7430K	

Spectacles

Aurora

Totally polycarbonate over specs with built-in side shields and brow guard and no metallic parts. Low energy impact protection at extreme environmental temperatures with UV protection. Can be worn over most glasses. Hang cord attachment points. Class 1.



	The state of the s				Brow Guard
(CE SP	Lens Type	Frame Colour	Order Code SSF-960	
	EN166 F	Clear	Clear	-0800K	

Wrop Around

Lens

RUTLAND Personal Protection Equipment

Safety Goggles

Class 1 optical performance. Wide angle of vision. Angle adjustment for strap enabling optimum position as well as use with a helmet or ear defenders. Wide comfort face flange. Can be worn over spectacles. Integrated foam face seal. Polycarbonate lens.





 Lens Type
 Frame Colour
 Order Code RTL-960

 Polycarbonate
 Clear
 -7520K

KENNEDY Scratch Resistant/Anti-Mist Safety Goggles

All goggles have a wide field of vision, built-in brow and cheek protection, soft PVC frame with an anatomically shaped bridge to adapt to all faces. All lenses provide UV protection. All frames will protect against liquid droplets and/or splashes. Fitted with wide anallergic elastic headbands and a one piece replaceable scratch resistant, anti-mist clear lenses.

Tiger

Medium energy impact protection. Smoke coloured frame with a polycarbonate lens and are lined with soft foam for user comfort and increased adherence. The lens is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solid). The frame has an indirect ventilation system and is resistant to liquids (drops and splashes) and penetration of hot solids.



Clear framed goggles are resistant to gross particles (dust particles >5 microns) and gas and fine particles (gas vapours, splashes, smokes and dust particles <5 microns.

Scorpion

Medium energy impact protection. Clear frame with a 2mm thick polycarbonate lens. The lens and the frame is resistant to molten metals and hot solids (splashes of molten metals and penetration of hot solids).

Lion

Low energy impact protection at extreme temperatures. Clear frame with an extremely flexible acetate lens.



Type	Lens	Frame	Order Code
	(Scratch resistant)	Colour	KEN-960
Scorpion	Polycarbonate	Clear	-8070K
Lion	Acetate	Clear	-8080K



Туре	Lens (Scratch Resistant)	Frame Colour	Order Code KEN-960	
Tiger	Polycarbonate	Smoke	-8140K	



ens

Scratch





Lens Type	Frame Colour	Order Code KEN-960
Scratch Resistant	Red	-8130K
Spare Lens		-8120K

Scratch Resistant/Anti-Mist Safety Goggles

Cobra

Low energy impact protection at extreme temperatures. UV protection against electrical arc discharges caused by a short circuit. Ultra light nylon frame with length adjustment the temples and front angle adjustment for low friction, lined with soft foam for user comfort and increased adherence. One piece, scratch resistant, anti-mist clear lens. As well as the arms having hang cord

Wide Headband

attachment points, a black universal hang cord is included with the goggles. Resistant to liquids (drops and splashes) and gross particles (dust particles >5 microns).



CE ST

Lens Frame Colour KEN-960
Scratch Resistant Blue -8060K

Hang Cord





EN166 B

Lens	Frame	Order Code
Type	Colour	TFF-960
Polycarbonate	Clear	-1250K

Anti-Dust Safety Goggles

Impact and dust resistant safety goggles are designed to protect the wearer from eye injury against moderate unspecified mechanical impact hazards. Single piece clear polycarbonate lens in a green tinted housing with an elasticated adjustment strap, direct ventilation. Class 1 optical clarity.



Maintenance & Personal Prote




Green

-0500K

Chemical Splash Resistant Safety Goggles

Anti-chemical splash, impact and dust resistant, direct ventilation safety goggles provide protection against chemical splashes and moderate unspecified mechanical impact hazards. Single piece clear polycarbonate lens in a green tinted housing with an elasticated adjustment strap. Class 1 optical clarity.





Lens Type	Frame Colour	Order Code SSF-960	
Polycarbonate	Green	-0520K	

Polycarbonate

Adjustable Face Screen

Clear full face screen with high impact polycarbonate browguard, djustable harness and replaceable sweatband. Clear polycarbonate face screen.
Class 1.




EN166 B



Description	TFF-960
Clear Face Shield Complete	-1500K

Face Screen Accessories







Green/ Clear Shade 3 Thine

Green Shade 3 Tritherm

CEB

EN166 B

Replacement Face ScreensTo fit TFF-960-1500K - 200mm depth. Green screens are shade 3 (Tritherm) for protection against infra red radiation and gas welding flare. Class 1.

Description	Order Code TFF-960	
All Clear Clear to Green All Green	-2500K -3200K -3220K	
Replacement Brow Guard		
Description	Order Code TFF-960	
Harness & Headband	-3240K	

Chin Guarde

To offer full face protection against particles and impact. Screen size: 160mm.

Description	Order Code TFF-960	
Chin Guard with Clear Screen	-2512K	
Replacement Clear Screen	-2514K	
Replacement Guard (No Screen)	-2518K	

SITESAFE Face Guard

Replaceable one piece clear polycarbonate lens which protects against chemical splashes, lens also has an aluminium edge. Built-in foam sweatband with a variable

setting on the crown support and a ratchet controlled headband adjuster with a pivoting full face and brow protection. Medium energy impact protection Class 1.



Lens	Order Code
Type	SSF-960
Clear	-9200K
Replacement Lens	-9220K

RUTLAND Face Shie

Liteguare

Comfortable and lightweight giving full facial protection. Easy adjustment of the crown strap. Simulated leather comfort band with foam backing. A choice of different screens are

available.
A pivot mechanism provides four different positions for the screen. An optional chinguard gives extended protection from below.

*Chinguard option requires compatible screen (LPC150). Class 3.



C	ϵ	8
E	N16	6 B

Description	RTL-960	
Clear Face Shield Complete	-4690K	
Accessories		
	Ordor Codo	

Order Code RTL-960	
-4620K	
-4640K	
-4630K	
-4650K	
-4670K	
-4600K	
-4680K	
	-4620K -4640K -4630K -4650K -4670K -4600K

GROUP HAND PROTECTION

Through the hand protection range, there are a number of quick reference logos to help you choose which level of safety is right for you. Below are the logos and their meanings.



Material is resistant to abrasions for greater protection.



Offers extra protection against low impact on the base of the wrist.



Resists the build-up and conductance of static electricity. Of most benefit when walking on synthetic carpets or near electrical machinery.



Designed to protect hands from refuse which may contain needles and glass.



Chemical resistant gloves for reducing the exposure of our hands to hazardous materials.



Offers extra insulation protection against cold objects.



Designed to protect hands from direct contact with sharp edges such as glass, metal, ceramics and other materials.



Offers protection against the level of voltage.



Added surface to provide extra grip during application.



Handling intermittently hot objects and materials in highheat environments.



Added surface to provide exeptional grip during application.



Glove is made from heavier material for greater wear and



Protective impact resistant gloves protect effectively the palms and wrists against traumatic impacts.



Used for inspection lines, can be made from lint-free material for less contamination.



Deters oil and grease and resists oil soak up where oil saturated gloves are a problem in many abrication plants.



Open backed gloves provide extra ventilation to the hand keeping it cooler throughout long periods of use.



Help prevent and relieve pain associated with RSI (repetitive strain injury).



Offers extra protection against low impact on the wrist or forearm.



Designed to protect hands from direct contact with sharp edges such as glass, metal, ceramics and other materials.



Designed for use where vibration can cause extreme and permanent damage to the hands.



Designed to protect the hand against sharp objects piercing the glove.

No two hands are alike. Finger length relative to palm size is not constant from person to person. Additionally what constitutes a comfortable fit can vary considerably between individuals. Using one of the methods below will help you to find an approximate glove size, but no method of measurement can substitute for actually trying them on.

Glove Sizing

Place you right hand as shown, with your index finger against the edge of this page. The measurement that follows the right side of your hand is your approximate glove size. For best results alway gauge at the widest point of the hand excluding the thumb. This is a general guide only.

Using a Tape Measure and the Sizing Guide

Wrap a tape measure around your hand at the widest point - excluding the thumb - (usually the knuckles) and make a loose fist. Note that measurement, round it to the nearest inch and refer to the sizing chart below to find your approximate glove size.

		Me	easur	ement		(Glove S	Size		
			6				X-Sma	all		
			7				Sma	II		
			8				Mediu	ım		
			9				Larg	е		
			10)			X-Larg	ge		
			11	L			XX-Lar	ge		
			12	2			XXX-La	rge		
	Glove	Size	XS	S	M	L	XL	XXL	XXXL	
	Sizing (auge	6	7	8	9	10	11	12	
492		PROD	UCTS	ARE ON	ILY AV	MILABLE	VIA YO	UR DIS	TRIBUT	OI

Gloves with this designation offer protection against light cuts, contusions, abrasions and mild detergents. Suitable for areas of 'minimal risk' where the effects on hands without gloves would be easily reversible or superficial. These products are unmarked and self-certified.



TFF-961 -1010K

-1000K

TFF-961

-1043K



Size	Weight per 12	Order Code TFF-961	
9	3.0kg	-1020K	

Mixed Fibre Gloves

9



2.60kg

700g



Cotton Micro-dot Gloves

100% cotton gloves

For Minima Risk Only



Size	Weight per 12	Order Code TFF-961	
9	1.10kg 1.10kg	-1050K -1055K	

Cotton Gloves

8



Size	Weight per 12	Order Code TFF-961	
9	740g	-1045K	

with micro-dot covered palm, thumb and forefinger. Knitted wrist.

Size	Weight per 12	Order Code TFF-961	
8	740g	-1042K	

TFF-961

-1060K -1080K

Foam Insulated Gloves

Fluorescent PVC coated foam insulated gloves with jersey lining and knitted wrists.





Size	Weight per 10	Order Code TFF-961	
10	910g	-1540K	

Terry Towelling Gauntlets

10

Thick close terry-towelling loop pile gloves which cushion and protect, also giving good

24oz 32oz





Maintenance & Personal

Size	Weight per 10	Order Code TFF-961	
10	32oz	-1095K	

Hot Mill Gloves

Canvas fleece double palms, forefinger and thumb, with cotton drill back, knuckles and cuff.





Size	Weight per 10	Order Code TFF-961	
9		-1130K	

Open Cuff Single Palm Chrome Leather Gloves

With 2" open cuffs, easily removed.



1.10kg

-1180K

Open Cuff Double Palm Chrome Leather Gloves



Weight per 12 Order Code TFF-961 Size Palm 10 -1200K Double 2.10kg

Single

10



0.95kg

1.00kg

-1260K

-1280K

6oz

8oz

10oz

9





0.95kg

2.50kg

10





-1670K

-1122K



3kg

-1990K

10

Index finger protection



Risk Only		L	
Size	Weight per 12	Order Code TFF-961	
9	1.35kg	-1140K	

Leather Gloves Leather palms, cotton backs CONTRACTOR and knitted wrists. For general handling. CE For Minimal Risk Only

Order Code SSF-961

-1170K

Weight per 12

Size 9

Cotton Backed

Cotton Backed Leather Gloves Leather palms, cotton backs and knitted wrists. For general handling.





Chrome Leather Riggers

Maintenance & Personal Protectio

Two piece chrome leather palms with protection



Size	Weight per 12	Order Code TFF-961	
10	1.60kg	-1300K	



Nappa Palm Riggers

Nappa leather palm, knuckles and finger tips.



Colour	Weight per 12	Order Code TFF-961
Multi	1.70kg	-1330K
Single	1.60kg	-1340K



Heavy Duty Riggers

Reinforced with extra palm, index finger and thumb protection. Selected split leather palms, knuckles and



Ition Only		
Size	Weight per 12	Order Code TFF-961
10	2.00kg	-1320K

10 1.60kg -1270K Split Leather Riggers Leather palms, fleece lined with protection on finger tips and knuckles. 2" cuffs with arterial protection patches.

Order Code

SSF-961

NYLON LINED PALM Weight per 12

Size



Size	Weight per 12	Order Code TFF-961
10	1.90kg	-1310K

Weight per 12

Extra Grip Riggers

and dot impregnated thumb and index 'grip zone'. Ideal for handling board and sheet materials.

 ϵ

Size

Standard



Cowhide Drivers Gloves



Order Code TFF-961



-1358K

1.70kg

10 - Lined



Cold Resistant Riggers

Arctic

Maintenance &

Selected split leather palms, knuckles and



-1900K

Knitted Wrist Riggers

Selected split leather palms with protection on finger tips, knuckles and index finger.



Size	per 12	TFF-961	
10		-1370K	

Superior Riggers

Size 9

\$5. Selected split leather palms, knuckles and finger

4.20kg



Colour	Weight per 12	Order Code TFF-961
Red/White Blue/Gold	2.70kg 3.00kg	-1360K -1380K
Blue/Gold	3.00kg	-1380

HARD WEARING - FLEECE LINED









Itisk Only	THE RESIDENCE OF THE PARTY OF T	
Size	Weight Order Co per 12 TFF-96	
10	3.00kg -129 0	K

Lined Gauntlets

Selected split leather one piece backs. Fully lined, two piece lining, fleece hand and cotton cuff.







Red



-1620K



Lined Gauntlet with Reinforced Thumb

Selected split leather one piece backs. Fully lined, two piece - fleece hand and cotton cuff. Re-inforced thumb



		L
Size	Weight per 10	Order Code TFF-961
10		-1960K



-1610K

-1620K

250g 250g

Green Red

Ε

EN420

Page **690**

GROUP HAND PROTECTION

Intermediate Design (Category 2)

Gloves with this designation offer protection against heavier cuts, contusions, abrasions, tears and punctures. Suitable for areas of specific risk: abrasion, blade cuts, tear and puncture. The performance of the glove against these risks is listed below the symbol as shown below.

BS EN388 Mechanical Hazard Gloves

Mechanical hazards are associated with handling rough or sharp objects that could damage skin such as brick, concrete, glass, and sheet metal. Mechanical hazards are not associated with moving machinery. Gloves can be a hazard if there is a possibility they could snag in moving parts and put the user in danger.

Abrasion Resistant Gloves



- a) Abrasion resistance. Scale 1 (low) to 4 (high).
- b) Cut resistance. Scale 1 (low) to 5 (high).
- c) Tear resistance. Scale 1 (low) to 4 (high).
- d) Puncture resistance. Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.

Each Abrasion Resistant


glove has a rating - the higher the number, the greater the protection.











Puncture Resistant Gloves

Tear Resistant Gloves

a. b. C. d.

a. b. c. **d.**



a) Abrasion resistance. Scale 1 (low) to 4 (high).

b) Cut resistance. Scale 1 (low) to 5 (high).

c) Tear resistance. Scale 1 (low) to 4 (high).







Cut Resistant Gloves



a) Abrasion resistance. Scale 1 (low) to 4 (high).

b) Cut resistance. Scale 1 (low) to 5 (high).

- c) Tear resistance. Scale 1 (low) to 4 (high).
- d) Puncture resistance. Scale 1 (low) to 4 (high).
- 0 = Fail. X = No test carried out.

Each Cut Resistant glove has a rating - the higher the number, the greater the protection.















a) Abrasion resistance. Scale 1 (low) to 4 (high). b) Cut resistance. Scale 1 (low) to 5 (high).

d) Puncture resistance. Scale 1 (low) to 4 (high).

c) Tear resistance. Scale 1 (low) to 4 (high).

0 = Fail. X = No test carried out.







EN12477 Welding Gloves

Safety standard EN12477 defines relevant requirements and test methods for protective gloves for use in manual metal welding and allied processes. Under this standard, all gloves to be used for welding must be independently tested and certified by an official notified body, and must meet certain performance levels.

EN12477 Minimum Performance Levels for Welding Gloves

TEST:	TYPE A Mig (Mlnimum Standard)	TYPE B Tig/Argon
N388	MECHANICAL	
Abrasion Resistance	Level 2	Level 1
Blade Cut Resistance	Level 1	Level 1
Tear Resistance	Level 2	Level 1
Puncture Resistance	Level 2	Level 1
EN407	THERMAL	
Burning Behaviour Resistance	eLevel 3	Level 2
Contact Heat Resistance	Level 1	Level I
Convective Heat Resistance	Level 2	Level 2
Radiant Heat Resistance	Level x	Level x
Small Molten Metal		
Splash Resistance	Level 3	Level 2
Large Molten Metal Splash		
Resistance	Level x	Level x
N1149-2	ELECTRICAL SA	FETY
Dry Conditions		
Test for Welders	10 ⁶ ohms	10 ⁵ ohms

Gloves are tested for chemical content of leather, sizing and dexterity.

GENERAL

All welding gloves, which have passed the above tests are awarded an EC Test Certificate, and all packaging and labelling of gloves will show appropriate markings (Pictograms). In addition, all packaging will contain a 'User Information Sheet' which will indicate performance levels achieved

GLOVES WHICH DO NOT COMPLY SHOULD NOT **BE USED FOR WELDING PURPOSES**

Heavy Duty Welder's Gauntlet

Full five finger welders gauntlet manufactured from select split leather with a full cotton lining with a one piece back. Reinforced palm and thumb for increased wear with no exposed seams to burn. Kevlar® sewn throughout.



-1580K











White

8

9

10

-6311B

-6312C -6313D

-6314E



Seamless

Size	Colour	Order Code TFF-961	
6 7 8 9 10 101	Grey	-6320A -6321B -6322C -6323D -6324E -6325F	









Premium quality blue natural rubber coating on a seamless **100% Kevlar® liner**, provides excellent wet and dry grip whilst offering outstanding blade cut resistance and protection from mechanical hazards.



EN388 2.2.4.3



Size	Weight per 12	Order Code TFF-961
8		-6111B
9		-6112C
10		-6113D



-6002C

-6003D

Knitted Co	tton Gloves		
Heavyweight kn	itted		Abr Cut Level
cotton gloves w grip PVC lattice elasticated wris	and sts.		Tear 4 Punct 3
111000			Extra Grip
Crys III			
CE =			
EN388 3.1.4.3			
Size	Weight per 12	Order Code TFF-961	
9	1.20kg	-1240K	



10



-2770K





10







TFF-961



2.30kg

-1500K









-1390K

-1400K

-1460K

1.2kg

1.2kg

1.2kg

8

9

355mm



Colour	Size	Weight per box	Order Code TFF-961	
Blue	6 ^{1/} ₂ 7 ^{1/} ₂ 8 ^{1/} ₂ 9 ^{1/} ₂	0.80kg 0.89kg 1.25kg 1.35kg	-7010A -7011B -7012C -7013D	



Colour	Size	Weight per box	Order Code TFF-961	
	61/2	0.80kg	-7020A	
Clear	71/2	0.89kg	-7021B	
Clear	81/2	1.25kg	-7022C	
	91/2	1.35kg	-7023D	

Nitrile Disposable Gloves



Powdered: For use in medical, veterinary laboratory and food processing conditions. Powdering on inside for ease of donning and perspiration absorption.

Non powdered: For use in electronics, pharmaceutical, laboratory, medical, dental and food processing applications.

Size	Type	weight per box	Order Code TFF-961	
61/2			-4020A	
71/2	Powdered		-4021B	
81/2	Powdered		-4022C	
91/2			-4023D	
61/2			-4010A	
71/2	Powder		-4011B	
81/2	Free		-4012C	
91/2			-4013D	

Latex Disposable Gloves

Micro textured natural rubber latex disposable gloves. Finger hugging latex provides maximum dexterity, sensitivity and comfort. Made from 100% natural rubber latex textured for extra grip.



Size	Type	Weight per box	Order Code TFF-961	
7		0.80kg	-3120A	
8	Powdered	0.89kg	-3121B	
9	Powdered	1.25kg	-3122C	
10		1.40kg	-3123D	
7		0.80kg	-3110A	
8	Powder Free	0.89kg	-3111B	
9		1.25kg	-3112C	
10		1.40kg	-3113D	

Garden and Household Set x3 CE Contents: EN166 1 pair general purpose goggles, 3 pairs of extra grip cotton drill gloves, **x1** 5 pairs of disposable latex gloves, 1 pair of rubber knee pads. CE Weight per Set Order Code **TFF-961** Size PPP-2G -9002B

High Visibility Garments

The highways agency manual for all contractors working on main or trunk roads in the UK states: 'all those working on or near the roads should wear high visibility warning clothing' (class 2 or 3) complying to BS EN 471 paragraph 4.2.3(b). 'Shall have two horizontal bands of retro-reflective material not less than 50mm apart from around the torso and bands of retro-reflective material joining the uppermost torso band from front to back over each shoulder'. In addition on motorways or other high speed roads full length sleeved garments should also comply with paragraph 4.2.4 'full length sleeves'.

EN471 Classifications

Three classifications based on conspicuity provided with each class denoting amounts of background and reflective material required.

Class 3 (Highest Level)

Bands of Reflective material shall not be less than 50mm wide.

Minimum Background material 0.80m². Minimum Reflective material 0.20m².

Class 2 (Medium Level)

Bands of Reflective material shall not be less than 50mm wide. Minimum Background material 0.50m². Minimum Reflective material 0.13m².

Class 1 (Lowest Level)

Bands of Reflective material shall not be less than 50mm wide. Minimum Background material 0.14m² Minimum Reflective material 0.10m². Minimal Risk/Off Road etc when enhanced visibility is required.

Waterproof High Visibility Coats

Satin yellow PU coated polyester with fixed nylon quilted lining. Two internal breast pockets, two exterior pockets with storm flaps and rear access for corporate identity logo heat attachment. Heavy weight two way zip with studded storm flap knitted storm cuffs, concealed hood with draw-string. Fully taped seams. All highway jackets have 2x 50mm sleeve bands.

Yellow



All tape bands are 50mm wide. EN343 EN471

These garments comply with the logarithms 89/686/EEC and the above reference standards. These garments comply with the requirements of Directive

Bands		Size	Weight	Order Code		
	Body	Braces	Size	each	TFF-962	
Ī	2	✓	M	0.9kg	-4011B	
	2	✓	L	1.0kg	-4012C	
	2	✓	XL	1.0kg	-4013D	
	2	✓	XXL	1.2kg	-4014E	



layers of clothing. If bulkier clothing has to be worn underneath a These garments comply with the requirements of Directive 89/686/EEC and the above reference standards. Sizing Guide

Olemb datas					
Size		Chest (ins)	Chest (cms)	Height	
	M	37-39	92-100	170-176	
	L	39-43	100-108	176-182	
	XL	43-46	108-116	182-188	
	XXL	46-49	116-124	188-194	

Fit according to chest size. This garment has a 20cm allowance built-in for comfort and to allow the garment to be worn over light

Ba Body	nds Braces	Size	Weight each	Order Code TFF-962	
2	✓	М	0.9kg	-4031B	
2	✓	L	1.0kg	-4032C	
2	✓	XL	1.0kg	-4033D	
2	✓	XXL	1.2kg	-4034E	

Available Sizes & Selection:

larger size may be required.

SPECIAL HAZARD CLOTHING

Waterproof **High Visibility Jackets**

Two hip pockets with velcro fastened flaps. Drawstring hood. Knitted storm cuffs. Two way zip front with studded storm flap. Inside pocket.

PREN343 1993:

Class 3 (highest) water penetration;

Class 1 (lowest) water vapour resistance

BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape

BSEN471 1994:

Class 2 retro reflective tape performance.

Available Sizes & Selection:

Fit according to chest size. This garment has a 20cm allowance built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.





Sizing Guide					
Size	Chest (inch)	Chest (cm)	Height		
М	37-39	92-100	170-176		
L	39-43	100-108	176-182		
XL	43-46	108-116	182-188		
XXL	46-49	116-124	188-194		



These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Bands		Cino	Weight	Order Code			
	Body	Braces	Size	each	TFF-962		
	2	✓	M	1.4kg	-4111B		
	2	✓	L	1.4kg	-4112C		
	2	✓	XL	1.4kg	-4113D		
	2	✓	XXL	1.4kg	-4114E		

Waterproof High Visibility Trousers

Satin yellow knitted polyester lightweight over-trousers with elasticated waist, velcro front fastening and fully taped waterproof seams. Complete with two 50mm reflective bands around each leg.

PREN343 1993:

Class 3 (highest) water penetration; Class 1 (lowest) water vapour resistance.


BSEN471 1994:

Class 1 area of fluorescent background and retro reflective tape.

BSEN471 1994: Class 2 retro reflective tape performance.







Colour	Size	Weight each	Order Code TFF-962	
Yellow	M L XL	330g 350g 360g	-4021B -4022C -4023D	
	XXL	370g	-4024E	
Orange	M L XL XXL	330g 350g 360g 370g	-4041B -4042C -4043D -4044E	



Available Sizes & Selection:

Fit according to waist size. This garment has a 20cm allowance built in for comfort and to allow the garment to be worn over light layers of clothing. If bulkier clothing has to be worn underneath, a larger size may be required.

SIZING GUIDE						
Size	Waist	Waist	Height			
Size	(inch)	(cm)	Height			
М	32-34	80-84	170-176			
L	34-36	88-92	176-182			
XL	36-38	82-96	182-188			
XXL	40-42	100-104	188-194			

Breathable High **Visibility Coats** Certified to EN471 Class 3 Certified to EN343 Class 2 breathing fabric. Polyester with PU coating. Concealed hood, full zip front with double storm flap. Nylon/polyester quilt lining, self double yoke back. Lower pockets with flap and elasticated storm cuffs. Stitched and welded seams. Reflective material.





EN343

These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Breathable

Size	weight each	TFF-962	
M	1050g	-4051B	
L	1050g	-4052C	
XL	1050g	-4053D	
XXL	1050g	-4054E	



Satin yellow knitted polyester. **High Visibility Yellow** All tape bands are 50mm wide.

BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape.

BSEN471 1994:

Class 2 retro reflective tape performance.



Breathable

EN471

Available Sizes & Selection:

Fit according to chest size. A larger size may be required if worn over clothing.

	Sizing Guid	le
Size	Chest (cm)	Height
M	112-116	152-194
L	116-120	152-194
XL	120-124	152-194
XXL	124-128	152-194



These garments comply with the requirements 89/686/EEC and the above reference standards. These garments comply with the requirements of Directive

Bag Body	nds Braces	Size	Weight each	Order Code TFF-962	
2	✓	М	150g	-4411B	
2	✓	L	200g	-4412C	
2	✓	XL	300g	-4413D	
2	✓	XXI	400g	-4414E	

Breathable High Visibility Trousers

Certified to EN471. Breathable fabric. Polyester with PU coating. Overtrousers with elasticated waist, tudded ankles. Reflective material.



FN471

These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Size	Weight each	Order Code TFF-962	
М	1050g	-4061B	
L	1050g	-4062C	
XL	1050g	-4063D	
XXL	1050g	-4064E	

High Visibility Body Warmers

Certified to EN471 Class 2. PU coating to hi-vis side. Reversible bodywarmer 'zipout'. Knitted collar. Heavy duty zip. Navy polycotton diamond quilt on reverse.





These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Size	Weight each	Order Code TFF-962
М	1050g	-4711B
L	1050g	-4712C
XL	1050g	-4713D
XXI	1050g	-4714F

High Visibility

Yellow knitted polyester. Elasticated neck. 50mm wide ScotchliteTM retro reflective bands. Single waist and two shoulder bands. Incorporates the convenience of a T-shirt with the safety of BS EN471. Treated with a wicking chemical to move moisture away from the skin to improve user comfort.



Size	Weight each	Order Code KEN-962	
Medium		-3502K	
Large		-3504K	
X/Large		-3506K	
XX/Large	:	-3508K	

EN471





These high visibility waistcoats from Tuffsafe® are manufactured from high quality lightweight satin polyester mesh, with 50mm retro-reflective bands and have Velcro® fastening at the front.

Directive 89/686/EEC and the above reference standards.

Yellow

All tape bands are 50mm wide.


BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape.

BSEN471 1994:

Class 2 retro reflective tape performance.

1 Body Band with Braces



These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Baı Body	nds Braces	Size	Weight each	Order Code TFF-962	
1	✓	М	135g	-4211B	
1	\checkmark	L	150g	-4212C	
1	\checkmark	XL	270g	-4213D	
1	\checkmark	XXL	350g	-4214E	
2	✓	S	135g	-4230A	
2	\checkmark	M	135g	-4231B	
2	✓	L	150g	-4232C	
2	✓	XL	270g	-4233D	
2	✓	XXL	350g	-4234E	
2	✓	XXXL	350g	-4235F	

High Visibility Waistcoat Manufactured to EN471 Class 2. 100% polyester with velcro



Directive 89/686/EEC and the above reference standards.

Available Sizes & Selection: Fit according to chest size. A larger size may be required if worn over clothing.

		Sizing Guide	
:	Size	Chest (cm)	Height
	М	112-116	152-194
	L	116-120	152-194
	XL	120-124	152-194
	XXL	124-128	152-194

'Hi-Vis' Orange

EN471

All tape bands are 50mm wide.


BSEN471 1994:

Class 3 area of fluorescent background and retro reflective tape.


BSEN471 1994:

Class 2 retro reflective tape performance.

1 Body Band with Braces







These garments comply with the requirements of Directive 89/686/EEC and the above reference standards.

Bar	nds	Size	Weight	Order Code	
Body	Braces	Size	each	TFF-962	
1	✓	M	135g	-4241B	
1	✓	L	150g	-4242C	
1	\checkmark	XL	270g	-4243D	
1	✓	XXL	350g	-4244E	
2	✓	S	150g	-4250A	
2	\checkmark	M	150g	-4251B	
2	\checkmark	L	270g	-4252C	
2	✓	XL	270g	-4253D	
2	✓	XXL	350g	-4254E	

Premium quality tradesman's jacket with front and back reflective beading that runs from cuff to cuff. Two front pockets and two breast pockets with 'Hook & Loop' fastening. Chunky front zip with storm flap with 'Hook & Loop' and press stud fasteners. Concealed drawstring hood. Adjustable cuffs with 'Hook & Loop' fastening and elasticated drawstring waist. Zip out quilt lining. Zipped embroidery access to allow corporate identity to be added. 300gsm heavyweight fabric. 65% polyester 35% cotton. Designed to coordinate with the Sicilia tradesman's trousers. (Jacket and Trousers illustrated together).

Colour: grey/black.



Size	Order Code TFF-962	
S	-6100A	
M	-6101B	
L	-6102C	
XL	-6103D	
XXL	-6104E	
XXXI	-6105F	



Premium Tradesman's Trousers

Premium quality, multi pocket work trousers with 11 different size pockets including a mobile phone pocket. Double hook and bar fastening waistband with zip fly and belt loops. Stitched seams and reinforced gusset with extra stitching on stress areas. External kneepad pockets. 300gsm heavyweight fabric. 65% polyester 35% cotton. Designed to co-ordinate with the Sicilia tradesman's trousers. (Jacket and trousers illustrated together).

Colour: grey/black.







	Size	Order Code	
	WxL	TFF-962	
		31 Inch	
	30" x 31"	-6140A	
	32" x 31"	-6141B	
	34" x 31"	-6142C	
	36" x 31"	-6143D	
	38" x 31"	-6144E	
	40" x 31"	-6145F	
		33 Inch	
	30" x 33"	-6160A	
f	32" x 33"	-6161B	
	34" x 31"	-6162C	
	36" x 33"	-6163D	
	38" x 33"	-6164E	
	40" x 33"	-6165F	

Winter Jacket

Trentino

Waterproof and abrasion resistant winter jacket with waterproof zip. Two zipped front pockets and two zipped inside breast pockets. Adjustable cuffs with 'Hook & Loop' fastening and elasticated drawstring waist. Foldaway drawstring hood concealed in the collar. 100% polyester lightweight Microfleece mesh lining with micro-knit body panels. PU coated. Durable Taslon outer fabric and Inner insulating fibre. Zipped embroidery access to allow corporate identity to be added.









	Colour	Size	Order Code TFF-962	
		S	-8500A	
		M	-8501B	
	Black	L	-8502C	
		XL	-8503D	
		XXL	-8504E	
		S	-8520A	
		M	-8521B	
	Navy	L	-8522C	
	,	XL	-8523D	
		XXI	-8524F	

Soft Shell Jacket

Roma

Lightweight, waterproof and wind resistant jacket with two zipped hip pockets and an outer zipped breast pocket with thru 'headphone' hole designed for use with personal stereos. Adjustable cuffs with 'Hook & Loop' fastening. Microfibre fleece lining and mesh lining. Elasticated drawstring inside waist. Zipped embroidery access to allow corporate identity to be added to breast area. 100% lightweight polyester.









Colour	Size	Order Code TFF-962	
	S	-8000A	
	M	-8001B	
	L	-8002C	
Black	XL	-8003D	
	XXL	-8004E	
	XXXL	-8005F	

Lightweight **Waterproof Jacket & Trousers**

Toscana

Lightweight, breathable and wind-resistant waterproof. Manufactured from 100% polyester. 110gsm micro fibre. PU coated/ mesh lining. Zipped embroidery access to allow corporate identity to be added. Contrast logo area on rear neckline. Designed to co-ordinate with the Toscana lightweight waterproof trousers.

Jacket

Two front pockets and two inside breast pockets all with zips and storm flaps. Elasticated cuffs with adjustable 'Hook & Loop' fastening. Elasticated drawstring hem. Concealed hood with elasticated drawstring.



Size	Weight each	Order Code TFF-962
S		-4820A
M		-4821B
L		-4822C
XL		-4823D
XXL		-4824E

Trousers

Two front pockets and one back pocket all with zips and storm flaps. 1/3 length leg zips allow these trousers to be put on/removed whilst wearing boots. Elasticated waistband with belt loops. Zip fly with double press-stud fasteners.





Size	Weight each	Order Code TFF-962	
S		-4860A	
M		-4861B	
L		-4862C	
XL		-4863D	
XXL		-4864E	

Padded Checked Workshirts



			and the same of th	
Colour	Size	Weight each	Order Code KEN-962	
	Medium	730g	-3700K	
Red	Large	740g	-3720K	
ricu	X-Large	790g	-3740K	
	XX-Large	830g	-3760K	
Dive	Large	740g	-3820K	
Blue	X-Large	790g	-3840K	
	Medium	730g	-3900K	
Green	Large	740g	-3920K	
diccii	X-Large	790g	-3940K	
	XX-Large	830g	-3960K	

Milano

Tradesman's

Heavyweight tradesman's trousers with two hip pockets, two rear pockets and internal knee pockets to support optional kneepads. Button fasten waistband with large belt loops and zip fly. Rear hanging loop. Double stitched seams and reinforced gusset. 300gsm heavyweight fabric. 65% polyester

35% cotton.

Colour: navy.



			77.8
Size	Weight each	Order Code TFF-962	
		31 " Leg	
30"		-6000A	
32"		-6001B	
34"		-6002C	
36"		-6003D	
		-6004E	
40"		-6005F	
		32" Leg	
30"		-6010A	
32"		-6011B	
34"		-6012C	
		-6013D	
		-6014E	
40"		-6015F	
	30" 32" 34" 36" 38" 40" 30" 32" 34" 36" 38"	30" 32" 34" 36" 30" 32" 34" 36" 32" 34" 36" 38"	Size each TFF-962 31" Leg 32" -6000A 32" -6001B 34" -6002C 36" -6003D 38" -6004E 40" -6005F 32" Leg 30" -6010A 32" -6011B 34" -6012C 36" -6013D 38" -6014E

Fleece Jackets

Front zip which matches the body colour. Two slanting front pockets which have pocket liners that are securely tacked to the bottom hem. Self-elasticated bottom hem. Twin needle




Size	Weight each	Order Code KEN-962	
Small	400g	-7100K	
Medium	400g	-7110K	
Large	400g	-7120K	
X-Large	400g	-7130K	
XX-Large	400g	-7140K	

Action Work Irousers

Poly-cotton work trousers (65% polyester, 35% cotton) with double stitched seams on for extra durability featuring hard wearing patches on the seat. Nine multi-sized pockets. Two side, two front, one leg and two back pockets - all zipped along with two open front pockets. Knee pad pockets with flap and top access. Button fastening with zipped fly and belt loops.

Colour: black.



Siena

Soft Microfleece jacket made from microfibres that make it water repellent and wind resistant. Two vertically zipped side pockets and one outer breast pocket. Fully lined with elasticated cuffs. Elasticated drawstring waist. Zipped embroidery access to allow corporate identity to be added. Antipilling treatment to prevent bobbling.



Colour	Size	Order Code TFF-962
	S	-4900A
	M	-4901B
Black	L	-4902C
	XL	-4903D
	XXL	-4904E
	XXXL	-4905F
	S	-4920A
	M	-4921B
Novac	L	-4922C
Navy	XL	-4923D
	XXL	-4924E
	XXXL	-4925F





Dry-Fit T-Shirts

Verona

Short sleeve T-shirt manufactured from 160gsm breathable polyester fabric and anti-static dry-fit material with Ciba® Wick Away' treatment that removes moisture away from the body. 100% polyester.





V-Neck	
--------	--

Colour	Size	Order Code TFF-962	
Black	S M L	-3600A -3601B -3602C	
	XL XXL	-3603D -3604E	

Round Neck

	•		
Colour	Size	Order Code TFF-962	
	S	-3560A	
	M	-3561B	
Navy	L	-3562C	
	XL	-3563D	
	XXL	-3564E	



Order Code

TFF-962 -3510A -3511B

-3512C

Size

Μ

Colour

Black/

Charcoal

Firenze

Classic heavyweight polo shirt with three button placket and colour matched buttons. Double knit pique weave with taped shoulder and neck seams and ribbed collar and cuffs. 230gsm heavyweight fabric. 65% polyester 35% cotton.

Colours: white, navy blue, sky blue, royal blue, red, burgundy, green and black.

Sizes range from small (37"/39") to XXXL (47"/49").















віаск	Burgunay	Green	Navy	Kea	
Colou	ır Size		Code - 962		
	S	-55	00A		
	M	-55	01B		
	L		02C		
Black	κ XL	-55	03D		
	XXL	-55	04E		
	XXXL	-55	05F		
	XXXXI	55	06G		
	S		20A		
	M		21B		
	L	-55	22C		
Burgun			23D		
	XXL		24E		
	XXXL		25F		
	XXXXI		26G		
	S		40A		
	M		41B		
	L		42C		
Greer			43D		
	XXL		44E		
	XXXL		45F		
	XXXXI		46G		
	S		60A		
	М		61B		
	L		62C		
Navy			63D		
	XXL	-55	64E		

Colour	Size	Order Code TFF-962
	S M	-5580A -5581B
	L IVI	-5581B -5582C
Red	XL	-5583D
	XXL	-5584E
	XXXL XXXXL	-5585F -5586G
-	S	-5600A
	M	-5601B
Royal Blue	L XL	-5602C -5603D
Royal blue	XXL	-5604E
	XXXL	-5605F
	XXXXL	-5606G
	S M	-5620A -5621B
	Ľ	-5622C
Sky Blue	XL	-5623S
	XXL XXXL	-5624E -5625F
	XXXXL	-5626G
	S	-5640A
	М	-5641B
White	L XL	-5642C -5643D
Willie	XXL	-5644E
	XXXL	-5645F
	XXXXL	-5646G



Premium Sweatshirt

Premium sweatshirt manufactured from 300gsm heavyweight fabric that has been treated for anti-pilling to help prevent bobbling. Elasticated wrists, waist and neckline. 65% polycotton, 35% cotton.





-5565F -5566G

Other Colours:
















Colour	Size	Order Code TFF-962	
	S	-7000A	
	M	-7001B	
Black	L	-7002C	
	XL	-7003D	
	XXL	-7004E	
	S	-7010A	
	M	-7011B	
Burgundy_	L	-7012C	
	XL	-7013D	
	XXL	-7014E	
	S	-7020A	
	M	-7021B	
Green	L	-7022C	
	XL	-7023D	
	XXL	-7024E	

Colour	Size	Order Code TFF-962	
	S	-7030A	
	M	-7031B	
Navy	L	-7032C	
	XL	-7033D	
	XXL	-7034E	
	S	-7040A	
	M	-7041B	
Royal	L	-7042C	
Blue	XL	-7043D	
	XXL	-7044E	



Caps — Full Panel Six-panel caps with cloth headbands. One size fits all. Waterproof plastic peak insert. Colour Colour Colour Colour Colour Colour Corder Code KEN-957 Red (Kobe logo) Black -3900K -3900K -4310K



WORKRANGER PROTECTION AT WORK

Royal Blue

Boiler Suite

-4350K

-4380K

Cotton Drill & Poly-cotton Boiler Suits

Hard wearing with breast pocket, two side swing pockets and front fastening. Suitable for garage, workshop, service, maintenance and many other applications.

Cotton drill. Colour: navy. Poly-cotton. Colour: royal blue.



Fabric	Size	Weight each	Order Code KEN-962	
	36"/38"	600g	-0360K	
Navy	40"/41"	600g	-0400K	
Cotton	42"/44"	780g	-0440K	
Drill	46"/48"	900g	-0480K	
	50"	900g	-0500K	
	36"/38"	650g	-1360K	
Royal Blue	40"/41"	770g	-1400K	
Poly-	42"/44"	830g	-1420K	
Cotton	46"/48"	950g	-1460K	
	50"	980g	-1500K	

TUFFSAFE. Waterproof

100% waterproof hooded jacket with drawstring closure, storm front with plastic zipper, raglan sleeves with wind cut off, patch pockets with flap in the front and vented cape back and underarm vents for improved user comfort. The trousers have elasticated waist band, no fly front and press stud ankle adjustment.



Colour	Size	Weight each	Order Code TFF-962	
·	S	1.00Kg	-5010A	
Green	M	1.05Kg	-5011B	
arcen	L	1.10Kg	-5012C	
	XL	1.20Kg	-5013D	
	S	1.00Kg	-5020A	
Orange	M	1.05Kg	-5021B	
Orange	L	1.10Kg	-5022C	
	XL	1.20Kg	-5023D	
	S	1.00Kg	-5030A	
Yellow	M	1.05Kg	-5031B	
TCHOW	L	1.10Kg	-5032C	
	XL	1.20Kg	-5033D	

Protection

KENNEDY Neoprene Gel Elbow Pads

Quick release velcro fastening One size fits all. Flexible straps for added comfort. Gel filled pad absorbs impact.



Size	Weight	Order Code	
(mm)	each	KEN-962	
150 x 190		-5020K	

Moulded Rubber Knee Pads

Heavy duty. One piece construction. Manufactured from black rubber. Deep ribbed contact zone to reduce the risk of slipping. Five point adjustable elasticated



strap. Conforms to, and is stamped CE. Suitable for regular use, industrial and professional applications.

Size	Weight	Order Code	
(mm)	each	KEN-962	
135 x 155		-4930K	

Moulded Rubber Knee Pads

Standard duty. One piece construction. Manufactured from black rubber. Ribbed contact zone to reduce the risk of slipping. Three point adjustable rubber strap. Suitable for occasional use, DIY and gardening applications.



Size	Weight	Order Code	
(mm)	each	KEN-962	
135 x 130		-4950K	

One Strap Knee Pads

Chrome leather with one strap.



Size (mm)	Weight each	Order Code KEN-962	
200 Dia.	220g	-4960K	

High Density Foam Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-marring face protects surfaces. Non-skid material helps avoid slipping. Lightweight design for comfort when standing.



Size	Weight	Order Code	
(mm)	each	KEN-962	
145 x 250	200g	-4980K	

Heavy Duty Knee Pads

Heavy duty chrome leather with two straps.



Size	Weight	Order Code	
(mm)	each	KEN-962	
195 x 215	430g	-4920K	

Black Leather Knee Pads

Heavy duty. A robust construction with buckle straps and a felt padding lining for added comfort.



Size	Weight	Order Code	
(mm)	each	KEN-962	
160 x 130		-4940K	

Partial Hard Case Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-marring face protects surfaces. Foam cushion beneath cap absorbs impact.



Size	Weight	Order Code	
(mm)	each	KEN-962	
180 x 250	200g	-4990K	

Neoprene Gel Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee.



Full Hard Case Knee Pads

Quick release velcro fastening. One size fits all. Flexible straps prevent binding behind the knee. Non-skid material helps avoid slipping. Nonmarring face protects surfaces. Foam cushion beneath cap absorbs impact.





Size (mm)	Weight each	Order Code KEN-962	
.85 x 235		-5000K	